

CONTAMINATION CONTROL

Portable Particle Counters



Features and Benefits

- 0.5 to 25 µm size range
- Up to six channels of simultaneous data
- 3.53 CFM (100 L/min) flow rate
- Complies with all requirements of ISO 21501-4
- Best choice for filter testing in clean rooms
- 10,000 sample record storage, 999 locations
- Ethernet and USB outputs
- Industry's loudest audible alarm
- Easy icon-driven touch screen operation
- Reports for ISO-14644-1, EU GMP Annex 1, and FS209E
- Allows storage and recall of specific tests/recipes
- Displays up to three environmental parameters
- Stainless steel enclosure
- Lightweight
- Stand-alone or integrate into a facility monitoring system
- Clean room classification down to ISO Class 2

AEROTrak™ Portable Particle Counter Model 9500

The TSI AEROTrak™ 9500 Portable Particle Counter offers best-in-class features and versatility. Perform ISO 14644-1 classifications and complete certifications of EU GMP facilities by sampling 1 m³ of air in just 10 minutes! Compatible with TSI's accurate ventilation probes that measure air velocity/temperature/RH, the Model 9500 is a complete solution for your certification needs. The combination of an optional electronic filter scanner with up to 26 ft of tubing, make this the best instrument for in-place filter testing.

This particle counter can generate pass/fail reports for ISO 14644-1, EU GMP Annex 1, and FS209E. It can be used as a stand-alone particle counter or integrated into a facility monitoring system like TSI's FMS 5.

The Model 9500 complies with all the stringent requirements set forth in ISO 21501-4. It is calibrated with NIST traceable PSL spheres using TSI's world-class Classifier and Condensation Particle Counters, the recognized standard for particle measurements. Backed with a standard two-year warranty and TSI's long-standing reputation for high quality, there are no other particle counters like it on the market today.



TRUST. SCIENCE. INNOVATION.

Specifications

Model 9500

AEROTrak™ Portable Particle Counter

Features	9500
Size Range	0.5 to 25 µm
Particle Channel Sizes	0.5, 0.7, 1.0, 3.0, 5.0, 10.0 µm (additional channel sizes available)
Size Resolution	<15% @ 0.5 µm (ISO 21501-4)
Counting Efficiency	50% at 0.5 µm, 100% for particles > 0.75 µm (per ISO 21501-4 and JIS)
Concentration Limit	>100,000/ft³ at 5% coincidence loss
Light Source	Long life laser diode
Zero Count	<1 count per 5 minutes (per ISO 21501-4 and JIS B9921)
Flow Rate	3.53 CFM (100 L/min) ±5% accuracy (meets ISO 21501-4 and JIS B9921)
Flow Rate Control	Electronic, automatic closed loop (patented* flow control technology)
Sample Tube Extension	Up to 26.2 ft (8 m)
Sampling Modes	Manual, automatic, beep; cumulative/differential; count or concentration
Sampling Time	1 second to 99 hours
Sampling Frequency	1 to 9999 cycles or continuous
Exhaust	Internal HEPA filter
Vacuum Source	Internal pump
Communication Mode	Modbus® TCP over Ethernet or USB
Data Storage	10,000 sample records: includes date, time, six particle channels, flow, ID, and sample volume; transferable via USB data download or TrakPro™ Lite software
Audible Alarm	Built-in; >85 dB at 1 meter (adjustable)
Status Indicators	Low battery, flow, laser
Alarm Output	Dry contacts, closed when alarm is engaged
Alarm Limits	Programmable for all particle channels
Display	VGA 5.7-inch (14.5 cm) touch-screen display
Languages	English, German, French, Spanish, Japanese, Chinese (simplified), Italian
Printer	Built-in thermal printer (also available without printer)
Printer Output	Prints in all available languages
Environmental Sensor Interface	Supports TSI Probe Models: 960, 962, 964, 966 (air velocity/temp/RH) and Temp/RH probe

Features	9500
Software	Compatible with TrakPro™ Lite and FMS 5 software
Unit ID	Configurable IP address
Security	2-level password protection to lock out usage and configuration
Location ID	Up to 999 Locations; 16 characters long
Reports	Provides Pass/Fail on ISO 14644-1, EU GMP, and FS209E reports
Calibration	NIST traceable using TSI calibration system
Calibration Frequency	Recommended minimum of once per year
Dimension (H x W x D)	9.5 in. x 9.0 in. x 9.2 in. (24.1 cm x 23.0 cm x 23.2 cm) (without isokinetic inlet)
Weight	14.2 lbs (6.44 kg) with two batteries
Power	110 to 240 VAC universal power supply
Battery	Removable/rechargeable Li-Ion batteries (2 battery slots)
Battery Life	>2 hours of continuous operation
Battery Recharge	4 hours (when idle)
External Surface	Stainless steel
Operating Range	41° to 95°F (5° to 35°C), 20% to 95% noncondensing
Storage Range	32° to 122°F (0° to 50°C), up to 98% RH noncondensing
Standards	ISO 21501-4, CE, JIS B9921
Warranty	Two years, extended warranties available
Included Accessories	Printed QuickStart guide, operating manual on CD, power supply, battery, barbed inlet, isokinetic probe, tripod, tubing, purge filter, printer paper, USB cable and TrakPro™ Lite software
Optional Accessories	Electronic filter scanning probe, basic filter scanning probe, TSI velocity probes, Temp/RH probe, additional battery, dual port external battery charger, isokinetic probes, isokinetic inlets, sample tubing, carrying case

*Patent Number 6,167,107

Specifications are subject to change without notice. TSI, the TSI logo, AeroTrak, and TrakPro are trademarks of TSI Incorporated. Modbus is a registered trademark of Modicon, Inc.

TSI Incorporated - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA Tel: +1 800 874 2811

E-mail: info@tsi.com

Website: www.tsi.com

UK Tel: +44 149 4 459200

E-mail: tsuik@tsi.com

Website: www.tsiinc.co.uk

France Tel: +33 491 11 87 64

E-mail: tsifrance@tsi.com

Website: www.tsiinc.fr

Germany Tel: +49 241 523030

E-mail: tsigmbh@tsi.com

Website: www.tsiinc.de

India Tel: +91 80 41132470

E-mail: tsi-india@tsi.com

China Tel: +86 10 8251 6588

E-mail: tsibeijing@tsi.com

Singapore Tel: +65 6595 6388

E-mail: tsi-singapore@tsi.com



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website www.tsi.com for more detailed specifications.